

HIN0500

SERIES

A Toyota Group Company









RANGE / SERIES	HINO 500
MODEL NAME	1927 Auto
MODEL CODE	GH8JM7A
DRIVE SYSTEM	4 x 2 (6W)
GROSS VEHICLE WEIGHT (Kg)	18,200
GROSS COMBINATION MASS (Kg)	N/A
TRANSMISSION	6-Speed A/T with Overdrive
TIRES & RIMS	11.00R20-16
FUEL TANK CAPACITY (L)	200
DIMENSIONS	
Wheelbase (mm)	5,080
Length (mm)	8,835
Width (mm)	2,490
Height (mm)	2,765
ENGINE	
Model	J08E-WE
Emission Standard	Euro 4
Max. Engine Speed (rpm)	2,600
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled
Combustion System	Direct Injection Type
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	7.684
PERFORMANCE	
Max. Output (PS) ISO Net JIS Gross	260 265
Max. Torque (Nm) ISO Net JIS Gross	794 804
Max. Speed (kph)	100
SUSPENSION	
Front	Semi-elliptic Leaf Springs with Single Acting Shock Absorbers
Rear	Semi-elliptic Main and Auxiliary Leaf Springs
BRAKES	
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type, Equipped with ABS
(Features)	Leading and Trailing Shoes for Front and Rear Wheels







Air-operated Spring Brake Acting on Rear Axle

Parking