

HINO500 SERIES









RANGE / SERIES	HINO 500
MODEL NAME	2629 6x2
MODEL CODE	FL8JW7A
DRIVE SYSTEM	6 x 2 (10W)
GROSS VEHICLE WEIGHT (Kg)	26,000
GROSS COMBINATION MASS (Kg)	N/A
TRANSMISSION	9-Speed M/T, Direct-drive
TIRES & RIMS	11.00R22.5
FUEL TANK CAPACITY (L)	320
DIMENSIONS	
Wheelbase (mm)	6,130 + 1,350
Length (mm)	11,935
Width (mm)	2,490
Height (mm)	2,770
ENGINE	
Model	J08E-WD
Emission Standard	Euro 4
Max. Engine Speed (rpm)	2,600
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled
Combustion System	Direct Injection Type
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	7.684
PERFORMANCE	
Max. Output (PS) ISO Net JIS Gross	280 285
Max. Torque (Nm) ISO Net JIS Gross	824 834
Max. Speed (kph)	111
SUSPENSION	
Front	Semi-elliptic Leaf Springs (Reinforced Type) with Single Acting Shock Absorbers
Rear	Semi-elliptic Leaf Springs (Reinforced Type)
BRAKES	
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type, Equipped with ABS
(Features)	Leading and Trailing Shoes with Auto Brakeshoe Adjuster
Parking	Air-operated Spring Brake Acting on Front and 1st Rear Axle





