

## HIN0700

SERIES









RANGE / SERIES	HINO 700
MODEL NAME	2846 Tractor
MODEL CODE	SS1EKSA
DRIVE SYSTEM	6 x 4 (10W)
GROSS VEHICLE WEIGHT (Kg)	28,300
GROSS COMBINATION MASS (Kg)	60,000
TRANSMISSION	16-Speed, Overdrive, Synchromesh 1st - 16th
TIRES & RIMS	295/80R22.5-16PR
FUEL TANK CAPACITY (L)	400
DIMENSIONS	
Wheelbase (mm)	3,300 + 1,310
Length (mm)	7,005
Width (mm)	2,490
Height (mm)	3,325
ENGINE	
Model	E13C-UR
Emission Standard	Euro 4
Max. Engine Speed (rpm)	2,130
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled
Combustion System	Direct Injection Type
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	12.913
PERFORMANCE	
Max. Output (PS)	450   460
ISO Net   JIS Gross	400   400
Max. Torque (Nm) ISO Net   JIS Gross	1,912   1,952
Max. Speed (kph)	125
SUSPENSION	
Front	Semi-elliptic Tapered Leaf Springs with Shock Absorbers
Rear	Semi-elliptic Tapered Leaf Springs with Shock Absorbers and Torque Rods
BRAKES	
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type
(Features)	Leading and Trailing Shoes for Front and Rear Wheels with Auto Brakeshoe Adjuster and ABS
Parking	Spring Brake Acting on Front and Rear Frontward Wheels





