



HINO

A Toyota Group Company



XZU342L

HINO300
SERIES



A Toyota Group Company

LIGHT-DUTY 300 SERIES



MODELS	XZU342L		
	XZU342LC	XZU342LM	XZU342LH
DRIVE SYSTEM	4 x 2 (4W)	4 x 2 (6W)	
CAB	Narrow Cab		
GROSS VEHICLE WEIGHT (Kg)	3,800	4,460	7,500
TRANSMISSION	5-Speed M/T with Overdrive		
TIRES & RIMS	7.50-15-12PR	7.50-16-14PR	
FUEL TANK CAPACITY (L)	100		
DIMENSIONS			
Wheelbase (mm)	3,405	3,380	
Length (mm)	6,430	6320	
Width (mm)	1,720	1,955	
Height (mm)	2,115	2,155	
ENGINE			
Model	N04C-VC		
Emission Standard	Euro 4		
Max. Engine Speed (rpm)	3,100		
Type	Diesel, 4-Cycle, Vertical, Inline, 4-Cylinder, Overhead Valve, Water-cooled		
Combustion System	Direct Injection Type		
Fuel Injection System	Electronic Control Common Rail Type		
Displacement (L)	4.009		
PERFORMANCE			
Max. Output (PS) ISO	136		
Max. Torque (Nm) ISO	390		
Max. Speed (kph)	134	118	
SUSPENSION			
Front	Semi-elliptic Leaf Springs with Double Action Shock Absorbers		
Rear	Semi-elliptic Leaf Springs with Double Action Shock Absorbers	Semi-elliptic Main and Auxiliary Leaf Springs with Double Action Shock Absorbers	
BRAKES			
Service (Type)	Hydraulic System, Dual-Circuit, Vacuum Assist		
(Features)	2 Leading Shoes for Front and Rear Wheels		
Parking	Mechanical, Internal Expanding, Acting on Transmission Output Shaft		

